

O-ring free PFA Spray Chamber and Endcap

Part of a complete o-ring free sample introduction system for ICP and ICPMS

PFA PureChamber™

- Chemically inert PFA Teflon® construction results in low contamination and long life time.
- High transmission with excellent short-term and long-term stability.
- Available in high sample flow rate (>0.5 mL/min) and low sample flow rate versions (<0.5 mL/min).
- Secure leak free threaded drain port

PFA PureCap™

- Chemically inert PFA Teflon® construction results in low contamination and long life time.
- O-ring free seal to PureChamber reduces contamination and provides an easy to clean low maintenance system.
- Adapts and seals to any 6 mm o.d. nebulizer, ideal for use with PFA
- Additional threaded auxiliary port for addition gas.



The PFA PureChamber spray chamber and o-ring free PureCap endcap.

Teflon® is a registered trademark of DuPont

PFA PureChamber Spray Chamber for Aggressive and High-Purity Samples

- Versions to fit all ICPMS and ICPAES instruments.
- 100% PFA Teflon construction minimizes contamination and chemical compatibility issues.
- Direct connection to ESI injectors. (12/5 socket adapter available for standard quartz torches.)
- Long-life, nearly unbreakable.



PFA PureCap Endcap

- Interfaces all 6 mm nebulizers to PFA PureChamber.
- Tight, o-ring-free connections reduce contamination and facilitate cleaning.
- A second orthogonal gas port available for adding a additional or mixed gases to the spray chamber.
- Ideal for organic solvent and high purity sample analysis.

